

Minutes of Pre-bid Meeting of the Re-Tender published for Supply, Installation & Integration, Management and Maintenance of Equipment for Virtual classrooms at ANM/GNM Schools and IGIMS College of Nursing in the state of Bihar.

1. With reference to the **Notice Inviting Tender (NIT) Reference No.:** - **13/SHSB/Virtual Classroom/ 2020-21** for Supply, Installation & Integration, Management and Maintenance of Equipment for Virtual classrooms at ANM/GNM Schools and IGIMS College of Nursing in the state of Bihar, published in leading newspapers [PR.10136 (Ni.Ni.) 2020-21] and uploaded on the website "<http://www.eproc.bihar.gov.in/BELTRON>" and "statehealthsocietybihar.org", the Pre-Bid meeting was held on **05/01/2021** at **11.00 AM** in the Conference Hall of the 'State Health Society, Bihar (SHSB), Pariwar Kalyan Bhawan, Sheikhpura, Patna'.
2. The following members of the Technical Committee were present in the Pre-bid Meeting:

(i) Dr. Kaushal Kumar, Director in Chief (Nursing), Health Services, Patna, Bihar	Chairman
(ii) Shri Khalid Arshad, Administrative Officer, State Health Society, Bihar	Member
(iii) Dr. Ravishankar Singh, Chief Medical Officer, ROHFW (GoI), Patna	Member
(iv) Shri. Yogendra Prasad, Additional Director (Finance), State Health Society Bihar	Member
(v) Dr. Y. N. Pathak, State Programme Officer, Nursing Cell, State Health Society, Bihar	Member Secretary
(vi) Shri Arvind Kumar, System Analyst-cum-Data officer, State Health Society, Bihar	Member
(vii) Ms. Anuja Daniel, Principal, College of Nursing, IGIMS, Patna	Member
(viii) Shri Sumit Biswas, Representative of SRU, Patna	Member
3. The officer/employee/representative of the following interested bidders participated in the pre-bid meeting physically and few of them participated virtually: -

1) M/s Pace Computer Services, kolkata	2) M/s Graphics Traders Pvt. Ltd., Patna
3) M/s Infosystems and Solutions Pvt. Ltd.	4) M/s Nspire Enterprises, Patna
5) M/s. Sigma Enterprises	6) M/s Vertiv Energy Private Limited
7) M/s. Sensheiser Electronics India Pvt. Ltd.	
4. The following queries/clarification were requested by the prospective bidders via email on shsbnursingcell@gmail.com:

Sr. No	NIT Reference	As published in NIT	Query/ Request of interested agencies	Clarifications/ Amendments Recommended by Technical Committee																																																																
1	Page 34-37, Point 6.a: 5 KVA Online UPS device, Appendix 1 – Technical Specification of Equipment/Software	<p>"5 KVA Online UPS"</p> <table border="1"> <thead> <tr> <th>Item Particulars</th> <th>Specifications</th> </tr> </thead> <tbody> <tr> <td colspan="2">Input</td> </tr> <tr> <td>Nominal Voltage</td> <td>200/208/220/230/240 VAC</td> </tr> <tr> <td>Input Power Factor</td> <td>> 0.99(full load)</td> </tr> <tr> <td colspan="2">Output</td> </tr> <tr> <td>Nominal Output voltage</td> <td>200/208/220/230/240 VAC</td> </tr> <tr> <td colspan="2">Transfer Time</td> </tr> <tr> <td>Transfer Time (Inverter to Bypass/ Bypass to Inverter)</td> <td>2~4ms</td> </tr> <tr> <td>Overall Efficiency (AC to AC) - Online (Double Conversion)</td> <td>Upto 95% (on 100% load)</td> </tr> <tr> <td colspan="2">Alarms</td> </tr> <tr> <td>Battery Rating & Count</td> <td>Bidder to specify Individual Battery Rating and Qty of Battery being offered.</td> </tr> <tr> <td>Charging Rate</td> <td>13.5 to 13.8V</td> </tr> <tr> <td>Interconnects</td> <td>The Battery Bank shall be provided with suitable size interconnect copper Flexible cables with connectors and leads till FCBC.</td> </tr> <tr> <td>Compliance</td> <td>ISO 9001:2008, JIS C 8702-1:2009/Battery of renowned brands only of make Exide, Amaron Quanta, Rocket, Panasonic, SF, HBL</td> </tr> <tr> <td>Battery recharge time (After complete discharge) to 90% Capacity</td> <td>3hour to 90%</td> </tr> <tr> <td>SNMP</td> <td>SNMP Port for UPS Monitoring should be provided as standard in the UPS.</td> </tr> </tbody> </table>	Item Particulars	Specifications	Input		Nominal Voltage	200/208/220/230/240 VAC	Input Power Factor	> 0.99(full load)	Output		Nominal Output voltage	200/208/220/230/240 VAC	Transfer Time		Transfer Time (Inverter to Bypass/ Bypass to Inverter)	2~4ms	Overall Efficiency (AC to AC) - Online (Double Conversion)	Upto 95% (on 100% load)	Alarms		Battery Rating & Count	Bidder to specify Individual Battery Rating and Qty of Battery being offered.	Charging Rate	13.5 to 13.8V	Interconnects	The Battery Bank shall be provided with suitable size interconnect copper Flexible cables with connectors and leads till FCBC.	Compliance	ISO 9001:2008, JIS C 8702-1:2009/Battery of renowned brands only of make Exide, Amaron Quanta, Rocket, Panasonic, SF, HBL	Battery recharge time (After complete discharge) to 90% Capacity	3hour to 90%	SNMP	SNMP Port for UPS Monitoring should be provided as standard in the UPS.	<p>The bidder has suggested below specifications:</p> <table border="1"> <thead> <tr> <th>Item Particulars</th> <th>Suggested Specifications</th> </tr> </thead> <tbody> <tr> <td colspan="2">Input</td> </tr> <tr> <td>Nominal Voltage</td> <td>220/230/240VAC (1-Phase)</td> </tr> <tr> <td>Input Power Factor</td> <td>Unity</td> </tr> <tr> <td colspan="2">Output</td> </tr> <tr> <td>Nominal Output voltage</td> <td>220/230/240VAC (1-Phase)</td> </tr> <tr> <td colspan="2">Transfer Time</td> </tr> <tr> <td>Transfer Time (Inverter to Bypass/ Bypass to Inverter)</td> <td>Synchronous transfer: ≤0ms Asynchronous transfer (default): ≤20ms</td> </tr> <tr> <td>Overall Efficiency (AC to AC) - Online (Double Conversion)</td> <td>>95%</td> </tr> <tr> <td colspan="2">Alarms</td> </tr> <tr> <td>Battery Rating & Count</td> <td>Battery: 26Ah*12V*16nos</td> </tr> <tr> <td>Charging Rate</td> <td>Float voltage: 2.25V/cell Boost voltage: 2.35V/cell</td> </tr> <tr> <td>Interconnects</td> <td>Nyvin cable between UPS to battery as per standard design practice</td> </tr> <tr> <td>Compliance</td> <td>Exide make, standard as per battery manufacturer</td> </tr> <tr> <td>Battery recharge time (After complete discharge) to 90% Capacity</td> <td>5-6 hrs to charge 90% battery capacity</td> </tr> <tr> <td>SNMP</td> <td>Inbuilt</td> </tr> </tbody> </table>	Item Particulars	Suggested Specifications	Input		Nominal Voltage	220/230/240VAC (1-Phase)	Input Power Factor	Unity	Output		Nominal Output voltage	220/230/240VAC (1-Phase)	Transfer Time		Transfer Time (Inverter to Bypass/ Bypass to Inverter)	Synchronous transfer: ≤0ms Asynchronous transfer (default): ≤20ms	Overall Efficiency (AC to AC) - Online (Double Conversion)	>95%	Alarms		Battery Rating & Count	Battery: 26Ah*12V*16nos	Charging Rate	Float voltage: 2.25V/cell Boost voltage: 2.35V/cell	Interconnects	Nyvin cable between UPS to battery as per standard design practice	Compliance	Exide make, standard as per battery manufacturer	Battery recharge time (After complete discharge) to 90% Capacity	5-6 hrs to charge 90% battery capacity	SNMP	Inbuilt	<p>No Change.</p> <p>(The bidders request is not accepted.)</p>
Item Particulars	Specifications																																																																			
Input																																																																				
Nominal Voltage	200/208/220/230/240 VAC																																																																			
Input Power Factor	> 0.99(full load)																																																																			
Output																																																																				
Nominal Output voltage	200/208/220/230/240 VAC																																																																			
Transfer Time																																																																				
Transfer Time (Inverter to Bypass/ Bypass to Inverter)	2~4ms																																																																			
Overall Efficiency (AC to AC) - Online (Double Conversion)	Upto 95% (on 100% load)																																																																			
Alarms																																																																				
Battery Rating & Count	Bidder to specify Individual Battery Rating and Qty of Battery being offered.																																																																			
Charging Rate	13.5 to 13.8V																																																																			
Interconnects	The Battery Bank shall be provided with suitable size interconnect copper Flexible cables with connectors and leads till FCBC.																																																																			
Compliance	ISO 9001:2008, JIS C 8702-1:2009/Battery of renowned brands only of make Exide, Amaron Quanta, Rocket, Panasonic, SF, HBL																																																																			
Battery recharge time (After complete discharge) to 90% Capacity	3hour to 90%																																																																			
SNMP	SNMP Port for UPS Monitoring should be provided as standard in the UPS.																																																																			
Item Particulars	Suggested Specifications																																																																			
Input																																																																				
Nominal Voltage	220/230/240VAC (1-Phase)																																																																			
Input Power Factor	Unity																																																																			
Output																																																																				
Nominal Output voltage	220/230/240VAC (1-Phase)																																																																			
Transfer Time																																																																				
Transfer Time (Inverter to Bypass/ Bypass to Inverter)	Synchronous transfer: ≤0ms Asynchronous transfer (default): ≤20ms																																																																			
Overall Efficiency (AC to AC) - Online (Double Conversion)	>95%																																																																			
Alarms																																																																				
Battery Rating & Count	Battery: 26Ah*12V*16nos																																																																			
Charging Rate	Float voltage: 2.25V/cell Boost voltage: 2.35V/cell																																																																			
Interconnects	Nyvin cable between UPS to battery as per standard design practice																																																																			
Compliance	Exide make, standard as per battery manufacturer																																																																			
Battery recharge time (After complete discharge) to 90% Capacity	5-6 hrs to charge 90% battery capacity																																																																			
SNMP	Inbuilt																																																																			

Sr. No	NIT Reference	As published in NIT	Query/ Request of interested agencies	Clarifications/ Amendments Recommended by Technical Committee																																												
1	Page 34-37, Point 6.a: 5 KVA Online UPS device, Appendix 1 – Technical Specification of Equipment/Software	<p>“5 KVA Online UPS” Continued ...</p> <table border="1" data-bbox="450 225 1021 1385"> <thead> <tr> <th>Item Particulars</th> <th>Specifications</th> </tr> </thead> <tbody> <tr> <td>Interface to BMS</td> <td>ModBus Card for connecting to UPS to BMS thru RS485 & monitoring thru BMS should be supported as optional purchase.</td> </tr> <tr> <td colspan="2">Physical</td> </tr> <tr> <td>Normal Operating Temperature</td> <td>0 to 40 deg C</td> </tr> <tr> <td>Storage Temperature</td> <td>-15 to 50 deg C</td> </tr> <tr> <td>Noise Level should reduce with Load (Mandatory)</td> <td>< 50 dbA at 1-meter distance</td> </tr> <tr> <td>Standard Package of UPS to include the following minimum accessories</td> <td>1. USB Cable 2. UPS to Battery Bank Cable 3. Battery Interlink Cable 4. Fuse Box 5. User Manual Print / CD</td> </tr> <tr> <td>Grounding</td> <td>UPS should have grounding arrangement.</td> </tr> <tr> <td>Manufacturer Certifications & Compliance (Mandatory)</td> <td>QMS: As per ISO 9001: 2008 EMS: As per ISO 14001: 2004 OSHAS: As per ISO 18001: 2007</td> </tr> <tr> <td>Product Safety Certifications (Mandatory)</td> <td>IEC 62040-1:2008 ESD: IEC61000-4-2: level4 RS: IEC61000-4-3: level3 EFT: IEC61000-4-4: level4 SURGE: IEC61000-4-5:level4 CS:IEC61000-4-6:level3 IEC61000-4-8 IEC 61000-2-2 EN 62040-2:2006 EN 61000-3-2:2009 EN 61000-3-3:2013</td> </tr> <tr> <td>Service Support</td> <td>Three Years Warranty PAN India Service Support of OEM should be available</td> </tr> </tbody> </table>	Item Particulars	Specifications	Interface to BMS	ModBus Card for connecting to UPS to BMS thru RS485 & monitoring thru BMS should be supported as optional purchase.	Physical		Normal Operating Temperature	0 to 40 deg C	Storage Temperature	-15 to 50 deg C	Noise Level should reduce with Load (Mandatory)	< 50 dbA at 1-meter distance	Standard Package of UPS to include the following minimum accessories	1. USB Cable 2. UPS to Battery Bank Cable 3. Battery Interlink Cable 4. Fuse Box 5. User Manual Print / CD	Grounding	UPS should have grounding arrangement.	Manufacturer Certifications & Compliance (Mandatory)	QMS: As per ISO 9001: 2008 EMS: As per ISO 14001: 2004 OSHAS: As per ISO 18001: 2007	Product Safety Certifications (Mandatory)	IEC 62040-1:2008 ESD: IEC61000-4-2: level4 RS: IEC61000-4-3: level3 EFT: IEC61000-4-4: level4 SURGE: IEC61000-4-5:level4 CS:IEC61000-4-6:level3 IEC61000-4-8 IEC 61000-2-2 EN 62040-2:2006 EN 61000-3-2:2009 EN 61000-3-3:2013	Service Support	Three Years Warranty PAN India Service Support of OEM should be available	<p>The bidder has suggested below specifications:</p> <table border="1" data-bbox="1048 256 1529 1155"> <thead> <tr> <th>Item Particulars</th> <th>Suggested Specifications</th> </tr> </thead> <tbody> <tr> <td>Interface to BMS</td> <td>Inbuilt</td> </tr> <tr> <td colspan="2">Physical</td> </tr> <tr> <td>Normal Operating Temperature</td> <td>0-50 deg C</td> </tr> <tr> <td>Storage Temperature</td> <td>- 25 to 55 deg C</td> </tr> <tr> <td>Noise Level should reduce with Load (Mandatory)</td> <td><55dBA</td> </tr> <tr> <td>Standard Package of UPS to include the following minimum accessories</td> <td>Shall be as per standard design practice</td> </tr> <tr> <td>Grounding</td> <td>Shall be as per standard design practice</td> </tr> <tr> <td>Manufacturer Certifications & Compliance (Mandatory)</td> <td>UPS is ISO 9001, ISO 14001, ISO 45001 certified</td> </tr> <tr> <td>Product Safety Certifications (Mandatory)</td> <td>As per IEC/EN 62040-1</td> </tr> <tr> <td>Service Support</td> <td>Standard 1 year warranty on UPS and 2 years on battery shall be provided</td> </tr> </tbody> </table>	Item Particulars	Suggested Specifications	Interface to BMS	Inbuilt	Physical		Normal Operating Temperature	0-50 deg C	Storage Temperature	- 25 to 55 deg C	Noise Level should reduce with Load (Mandatory)	<55dBA	Standard Package of UPS to include the following minimum accessories	Shall be as per standard design practice	Grounding	Shall be as per standard design practice	Manufacturer Certifications & Compliance (Mandatory)	UPS is ISO 9001, ISO 14001, ISO 45001 certified	Product Safety Certifications (Mandatory)	As per IEC/EN 62040-1	Service Support	Standard 1 year warranty on UPS and 2 years on battery shall be provided	<p>No Change.</p> <p>(The bidders request is not accepted.)</p>
Item Particulars	Specifications																																															
Interface to BMS	ModBus Card for connecting to UPS to BMS thru RS485 & monitoring thru BMS should be supported as optional purchase.																																															
Physical																																																
Normal Operating Temperature	0 to 40 deg C																																															
Storage Temperature	-15 to 50 deg C																																															
Noise Level should reduce with Load (Mandatory)	< 50 dbA at 1-meter distance																																															
Standard Package of UPS to include the following minimum accessories	1. USB Cable 2. UPS to Battery Bank Cable 3. Battery Interlink Cable 4. Fuse Box 5. User Manual Print / CD																																															
Grounding	UPS should have grounding arrangement.																																															
Manufacturer Certifications & Compliance (Mandatory)	QMS: As per ISO 9001: 2008 EMS: As per ISO 14001: 2004 OSHAS: As per ISO 18001: 2007																																															
Product Safety Certifications (Mandatory)	IEC 62040-1:2008 ESD: IEC61000-4-2: level4 RS: IEC61000-4-3: level3 EFT: IEC61000-4-4: level4 SURGE: IEC61000-4-5:level4 CS:IEC61000-4-6:level3 IEC61000-4-8 IEC 61000-2-2 EN 62040-2:2006 EN 61000-3-2:2009 EN 61000-3-3:2013																																															
Service Support	Three Years Warranty PAN India Service Support of OEM should be available																																															
Item Particulars	Suggested Specifications																																															
Interface to BMS	Inbuilt																																															
Physical																																																
Normal Operating Temperature	0-50 deg C																																															
Storage Temperature	- 25 to 55 deg C																																															
Noise Level should reduce with Load (Mandatory)	<55dBA																																															
Standard Package of UPS to include the following minimum accessories	Shall be as per standard design practice																																															
Grounding	Shall be as per standard design practice																																															
Manufacturer Certifications & Compliance (Mandatory)	UPS is ISO 9001, ISO 14001, ISO 45001 certified																																															
Product Safety Certifications (Mandatory)	As per IEC/EN 62040-1																																															
Service Support	Standard 1 year warranty on UPS and 2 years on battery shall be provided																																															

Sr. No	NIT Reference	As published in NIT	Query/ Request of interested agencies	Clarifications/ Amendments Recommended by Technical Committee																																
2	Page 37-40, Point 6.b: Online 3KVA UPS, Appendix 1 – Technical Specification of Equipment/Software	<p>“Online UPS 3KVA”</p> <table border="1"> <thead> <tr> <th data-bbox="450 225 658 256">Item Particulars</th> <th data-bbox="658 225 1021 256">Specifications</th> </tr> </thead> <tbody> <tr> <td data-bbox="450 256 658 699">Technology and Capability</td> <td data-bbox="658 256 1021 699"> a) True Online configuration with double conversion UPS & Zero transfer time. b) DSP based control with advanced technology. c) Wide Input voltage range from (80 ~ 280VAC) d) Auto restart capability with the Independent battery bank operation of the UPS. e) UPS should be designed at Rated PF of 0.8 i.e. 3kVA/2.4kW UPS rating. f) Generator compatibility with cold start and AC start features. </td> </tr> <tr> <td data-bbox="450 699 658 759">3kVA /2.4kW</td> <td data-bbox="658 699 1021 759">Make / Model / Part No to be specified by the vendor</td> </tr> <tr> <td data-bbox="450 759 658 879">Input Voltage Range</td> <td data-bbox="658 759 1021 879">220/230/240VAC Range (Full Load) 175~280VAC Range (Derating to 50%-100% Load) 80~175VAC</td> </tr> <tr> <td data-bbox="450 879 658 940">Output Voltage Distortion (THDu)</td> <td data-bbox="658 879 1021 940">< 3% for linear load & < 5% for non-linear load.</td> </tr> <tr> <td data-bbox="450 940 658 1059">Overall Efficiency (AC to AC) - Online (Double Conversion)</td> <td data-bbox="658 940 1021 1059">Upto 93% (at 100% load)</td> </tr> <tr> <td data-bbox="450 1059 658 1150">Inverter Overload capacity</td> <td data-bbox="658 1059 1021 1150"><105% for continuous, <105~<125for 1Min, <125~<150 for 30Sec</td> </tr> <tr> <td data-bbox="450 1150 658 1270">Battery Bank 12V x No. of Battery x Battery AH</td> <td data-bbox="658 1150 1021 1270">Minimum Bank AHC of 3000 AHC (12V x No. of Battery x Battery AH</td> </tr> </tbody> </table>	Item Particulars	Specifications	Technology and Capability	a) True Online configuration with double conversion UPS & Zero transfer time. b) DSP based control with advanced technology. c) Wide Input voltage range from (80 ~ 280VAC) d) Auto restart capability with the Independent battery bank operation of the UPS. e) UPS should be designed at Rated PF of 0.8 i.e. 3kVA/2.4kW UPS rating. f) Generator compatibility with cold start and AC start features.	3kVA /2.4kW	Make / Model / Part No to be specified by the vendor	Input Voltage Range	220/230/240VAC Range (Full Load) 175~280VAC Range (Derating to 50%-100% Load) 80~175VAC	Output Voltage Distortion (THDu)	< 3% for linear load & < 5% for non-linear load.	Overall Efficiency (AC to AC) - Online (Double Conversion)	Upto 93% (at 100% load)	Inverter Overload capacity	<105% for continuous, <105~<125for 1Min, <125~<150 for 30Sec	Battery Bank 12V x No. of Battery x Battery AH	Minimum Bank AHC of 3000 AHC (12V x No. of Battery x Battery AH	<p>The bidder has suggested below specifications:</p> <table border="1"> <thead> <tr> <th data-bbox="1048 256 1256 288">Item Particulars</th> <th data-bbox="1256 256 1529 288">Specifications</th> </tr> </thead> <tbody> <tr> <td data-bbox="1048 288 1256 349">Technology and Capability</td> <td data-bbox="1256 288 1529 349">110V-280V AC</td> </tr> <tr> <td data-bbox="1048 349 1256 410">3kVA /2.4kW</td> <td data-bbox="1256 349 1529 410">Vertiv make 3kVA GXTMT+CX LB</td> </tr> <tr> <td data-bbox="1048 410 1256 470">Input Voltage Range</td> <td data-bbox="1256 410 1529 470">110V-280V AC</td> </tr> <tr> <td data-bbox="1048 470 1256 561">Output Voltage Distortion (THDu)</td> <td data-bbox="1256 470 1529 561"><7% for non-linear load</td> </tr> <tr> <td data-bbox="1048 561 1256 681">Overall Efficiency (AC to AC) - Online (Double Conversion)</td> <td data-bbox="1256 561 1529 681">91% (AC to AC) 96% ECO Mode</td> </tr> <tr> <td data-bbox="1048 681 1256 772">Inverter Overload capacity</td> <td data-bbox="1256 681 1529 772">100%-110% for 10mins, 110%-130% for 1min 130% for 3sec</td> </tr> <tr> <td data-bbox="1048 772 1256 892">Battery Bank 12V x No. of Battery x Battery AH</td> <td data-bbox="1256 772 1529 892">Battery: 42Ah*12V*6nos</td> </tr> </tbody> </table>	Item Particulars	Specifications	Technology and Capability	110V-280V AC	3kVA /2.4kW	Vertiv make 3kVA GXTMT+CX LB	Input Voltage Range	110V-280V AC	Output Voltage Distortion (THDu)	<7% for non-linear load	Overall Efficiency (AC to AC) - Online (Double Conversion)	91% (AC to AC) 96% ECO Mode	Inverter Overload capacity	100%-110% for 10mins, 110%-130% for 1min 130% for 3sec	Battery Bank 12V x No. of Battery x Battery AH	Battery: 42Ah*12V*6nos	<p>No Change.</p> <p>(The bidders request is not accepted.)</p>
Item Particulars	Specifications																																			
Technology and Capability	a) True Online configuration with double conversion UPS & Zero transfer time. b) DSP based control with advanced technology. c) Wide Input voltage range from (80 ~ 280VAC) d) Auto restart capability with the Independent battery bank operation of the UPS. e) UPS should be designed at Rated PF of 0.8 i.e. 3kVA/2.4kW UPS rating. f) Generator compatibility with cold start and AC start features.																																			
3kVA /2.4kW	Make / Model / Part No to be specified by the vendor																																			
Input Voltage Range	220/230/240VAC Range (Full Load) 175~280VAC Range (Derating to 50%-100% Load) 80~175VAC																																			
Output Voltage Distortion (THDu)	< 3% for linear load & < 5% for non-linear load.																																			
Overall Efficiency (AC to AC) - Online (Double Conversion)	Upto 93% (at 100% load)																																			
Inverter Overload capacity	<105% for continuous, <105~<125for 1Min, <125~<150 for 30Sec																																			
Battery Bank 12V x No. of Battery x Battery AH	Minimum Bank AHC of 3000 AHC (12V x No. of Battery x Battery AH																																			
Item Particulars	Specifications																																			
Technology and Capability	110V-280V AC																																			
3kVA /2.4kW	Vertiv make 3kVA GXTMT+CX LB																																			
Input Voltage Range	110V-280V AC																																			
Output Voltage Distortion (THDu)	<7% for non-linear load																																			
Overall Efficiency (AC to AC) - Online (Double Conversion)	91% (AC to AC) 96% ECO Mode																																			
Inverter Overload capacity	100%-110% for 10mins, 110%-130% for 1min 130% for 3sec																																			
Battery Bank 12V x No. of Battery x Battery AH	Battery: 42Ah*12V*6nos																																			

Sr. No	NIT Reference	As published in NIT	Query/ Request of interested agencies	Clarifications/ Amendments Recommended by Technical Committee																																								
2	Page 37-40, Point 6.b: Online 3KVA UPS, Appendix 1 – Technical Specification of Equipment/Software	<p>“Online UPS 3KVA” Continued....</p> <table border="1"> <thead> <tr> <th data-bbox="450 225 658 256">Item Particulars</th> <th data-bbox="658 225 1021 256">Specifications</th> </tr> </thead> <tbody> <tr> <td data-bbox="450 256 658 316">Batteries Type</td> <td data-bbox="658 256 1021 316">Sealed Maintenance Free (SMF) - 12V Cells, VRLA, GEL</td> </tr> <tr> <td data-bbox="450 316 658 432">Charger type / Charging Method & Charging Voltages</td> <td data-bbox="658 316 1021 432">Constant Voltage Constant Current Solid state SMPS charger Float Charge 81.9V Boost Charge 84.0V</td> </tr> <tr> <td data-bbox="450 432 658 549">External charger board</td> <td data-bbox="658 432 1021 549">Additionally, install the 4A charger board to increase the charge current to reach at maximum 8A.</td> </tr> <tr> <td data-bbox="450 549 658 699">Battery recharge time (After complete discharge) to 90% capacity</td> <td data-bbox="658 549 1021 699">3 hour to 90%</td> </tr> <tr> <td data-bbox="450 699 658 758">Interface to Mini TVSS card</td> <td data-bbox="658 699 1021 758">This card enable the UPS with the surge protection (OPTIONAL)</td> </tr> <tr> <td data-bbox="450 758 658 908">Interface to BMS (Building Management System) - To be quoted as option</td> <td data-bbox="658 758 1021 908">ModBus Card for connecting to UPS to BMS thru RS485 & monitoring thru BMS (OPTIONAL)</td> </tr> <tr> <td data-bbox="450 908 658 1058">Interface to DCS (Distributed Control System) - To be quoted as option</td> <td data-bbox="658 908 1021 1058">Relay I/O Card or PFC (Potential free contacts) for connecting to UPS to DCS / PLC / SCADA system for communicating UPS operating status (OPTIONAL)</td> </tr> <tr> <td data-bbox="450 1058 658 1117">Operating Temperature</td> <td data-bbox="658 1058 1021 1117">0 to 40 deg C</td> </tr> <tr> <td data-bbox="450 1117 658 1176">Storage Temperature</td> <td data-bbox="658 1117 1021 1176">-15 to 50 deg C</td> </tr> </tbody> </table>	Item Particulars	Specifications	Batteries Type	Sealed Maintenance Free (SMF) - 12V Cells, VRLA, GEL	Charger type / Charging Method & Charging Voltages	Constant Voltage Constant Current Solid state SMPS charger Float Charge 81.9V Boost Charge 84.0V	External charger board	Additionally, install the 4A charger board to increase the charge current to reach at maximum 8A.	Battery recharge time (After complete discharge) to 90% capacity	3 hour to 90%	Interface to Mini TVSS card	This card enable the UPS with the surge protection (OPTIONAL)	Interface to BMS (Building Management System) - To be quoted as option	ModBus Card for connecting to UPS to BMS thru RS485 & monitoring thru BMS (OPTIONAL)	Interface to DCS (Distributed Control System) - To be quoted as option	Relay I/O Card or PFC (Potential free contacts) for connecting to UPS to DCS / PLC / SCADA system for communicating UPS operating status (OPTIONAL)	Operating Temperature	0 to 40 deg C	Storage Temperature	-15 to 50 deg C	<p>The bidder has suggested below specifications:</p> <table border="1"> <thead> <tr> <th data-bbox="1048 256 1256 288">Item Particulars</th> <th data-bbox="1256 256 1529 288">Specifications</th> </tr> </thead> <tbody> <tr> <td data-bbox="1048 288 1256 376">Batteries Type</td> <td data-bbox="1256 288 1529 376">Sealed Maintenance Free (SMF) - VRLA AGM type</td> </tr> <tr> <td data-bbox="1048 376 1256 494">Charger type / Charging Method & Charging Voltages</td> <td data-bbox="1256 376 1529 494">Float voltage: 2.25V/cell Boost voltage: 2.35V/cell</td> </tr> <tr> <td data-bbox="1048 494 1256 553">External charger board</td> <td data-bbox="1256 494 1529 553">Inbuild charger suitable to charge battery</td> </tr> <tr> <td data-bbox="1048 553 1256 703">Battery recharge time (After complete discharge) to 90% capacity</td> <td data-bbox="1256 553 1529 703">5-6 hrs to charge 90% battery capacity</td> </tr> <tr> <td data-bbox="1048 703 1256 762">Interface to Mini TVSS card</td> <td data-bbox="1256 703 1529 762">TVSS shall be provided</td> </tr> <tr> <td data-bbox="1048 762 1256 912">Interface to BMS (Building Management System) - To be quoted as option</td> <td data-bbox="1256 762 1529 912">UPS has only one communication slot. One card can be operated at a time.</td> </tr> <tr> <td data-bbox="1048 912 1256 1031">Interface to DCS (Distributed Control System) - To be quoted as</td> <td data-bbox="1256 912 1529 1031">UPS has only one communication slot. One card can be operated at a time.</td> </tr> <tr> <td data-bbox="1048 1031 1256 1090">Operating Temperature</td> <td data-bbox="1256 1031 1529 1090">Ambient Temp 0-50 deg C</td> </tr> <tr> <td data-bbox="1048 1090 1256 1149">Storage Temperature</td> <td data-bbox="1256 1090 1529 1149">up to 60 deg C</td> </tr> </tbody> </table>	Item Particulars	Specifications	Batteries Type	Sealed Maintenance Free (SMF) - VRLA AGM type	Charger type / Charging Method & Charging Voltages	Float voltage: 2.25V/cell Boost voltage: 2.35V/cell	External charger board	Inbuild charger suitable to charge battery	Battery recharge time (After complete discharge) to 90% capacity	5-6 hrs to charge 90% battery capacity	Interface to Mini TVSS card	TVSS shall be provided	Interface to BMS (Building Management System) - To be quoted as option	UPS has only one communication slot. One card can be operated at a time.	Interface to DCS (Distributed Control System) - To be quoted as	UPS has only one communication slot. One card can be operated at a time.	Operating Temperature	Ambient Temp 0-50 deg C	Storage Temperature	up to 60 deg C	<p>No Change.</p> <p>(The bidders request is not accepted.)</p>
Item Particulars	Specifications																																											
Batteries Type	Sealed Maintenance Free (SMF) - 12V Cells, VRLA, GEL																																											
Charger type / Charging Method & Charging Voltages	Constant Voltage Constant Current Solid state SMPS charger Float Charge 81.9V Boost Charge 84.0V																																											
External charger board	Additionally, install the 4A charger board to increase the charge current to reach at maximum 8A.																																											
Battery recharge time (After complete discharge) to 90% capacity	3 hour to 90%																																											
Interface to Mini TVSS card	This card enable the UPS with the surge protection (OPTIONAL)																																											
Interface to BMS (Building Management System) - To be quoted as option	ModBus Card for connecting to UPS to BMS thru RS485 & monitoring thru BMS (OPTIONAL)																																											
Interface to DCS (Distributed Control System) - To be quoted as option	Relay I/O Card or PFC (Potential free contacts) for connecting to UPS to DCS / PLC / SCADA system for communicating UPS operating status (OPTIONAL)																																											
Operating Temperature	0 to 40 deg C																																											
Storage Temperature	-15 to 50 deg C																																											
Item Particulars	Specifications																																											
Batteries Type	Sealed Maintenance Free (SMF) - VRLA AGM type																																											
Charger type / Charging Method & Charging Voltages	Float voltage: 2.25V/cell Boost voltage: 2.35V/cell																																											
External charger board	Inbuild charger suitable to charge battery																																											
Battery recharge time (After complete discharge) to 90% capacity	5-6 hrs to charge 90% battery capacity																																											
Interface to Mini TVSS card	TVSS shall be provided																																											
Interface to BMS (Building Management System) - To be quoted as option	UPS has only one communication slot. One card can be operated at a time.																																											
Interface to DCS (Distributed Control System) - To be quoted as	UPS has only one communication slot. One card can be operated at a time.																																											
Operating Temperature	Ambient Temp 0-50 deg C																																											
Storage Temperature	up to 60 deg C																																											

Sr. No	NIT Reference	As published in NIT	Query/ Request of interested agencies	Clarifications/ Amendments Recommended by Technical Committee																																								
2	Page 37-40, Point 6.b: Online 3KVA UPS, Appendix 1 – Technical Specification of Equipment/Software	<p>“Online UPS 3KVA” Continued...</p> <table border="1"> <thead> <tr> <th data-bbox="450 225 658 256">Item Particulars</th> <th data-bbox="658 225 1021 256">Specifications</th> </tr> </thead> <tbody> <tr> <td data-bbox="450 256 658 288">Operating Humidity</td> <td data-bbox="658 256 1021 288">5% ~ 95%RH (No Condensing)</td> </tr> <tr> <td data-bbox="450 288 658 320">Noise Level</td> <td data-bbox="658 288 1021 320">< 48 dbA at 1 meter distance</td> </tr> <tr> <td data-bbox="450 320 658 384">Dimension (w x d x h) in mm</td> <td data-bbox="658 320 1021 384">To be furnished by the vendor</td> </tr> <tr> <td data-bbox="450 384 658 416">Weight - in kg</td> <td data-bbox="658 384 1021 416">To be furnished by the vendor</td> </tr> <tr> <td data-bbox="450 416 658 576">Packaging Material/ Vibration Withstand & Drop Test</td> <td data-bbox="658 416 1021 576">Recyclable (No CFC) & 1. Vibration testing as per ISTA - 1G Non- operational with Packing</td> </tr> <tr> <td data-bbox="450 576 658 847">Standard Package of UPS to include the following minimum accessories</td> <td data-bbox="658 576 1021 847">1. UPS 2. CD - Monitoring Software 3. RS232 Cable 4. Tower Stand - For use as Tower 5. Brackets for mounting in 19" IT Server / Networking Rack 6. UPS to Battery bank connecting Cable 7. User Manual</td> </tr> <tr> <td data-bbox="450 847 658 927">Manufacturer Certifications</td> <td data-bbox="658 847 1021 927">QMS: As per ISO 9001: 2008 EMS: As per ISO 14001: 2004 OSHAS: As per ISO 18001: 2007</td> </tr> <tr> <td data-bbox="450 927 658 1294">Product Safety Certifications (Mandatory)</td> <td data-bbox="658 927 1021 1294">BIS Certification IEC 62040-1:2008 ESD: IEC61000-4-2: level4 RS: IEC61000-4-3: level3 EFT: IEC61000-4-4: level4 SURGE: IEC61000-4-5: level4 CS: IEC61000-4-6: level3 IEC61000-4-8 IEC 61000-2-2 EN 62040-2:2006 EN 61000-3-2:2009 EN 61000-3-3:2013</td> </tr> <tr> <td data-bbox="450 1294 658 1374">Service Support</td> <td data-bbox="658 1294 1021 1374">Three Years Warranty PAN India Service Support of OEM should be available</td> </tr> </tbody> </table>	Item Particulars	Specifications	Operating Humidity	5% ~ 95%RH (No Condensing)	Noise Level	< 48 dbA at 1 meter distance	Dimension (w x d x h) in mm	To be furnished by the vendor	Weight - in kg	To be furnished by the vendor	Packaging Material/ Vibration Withstand & Drop Test	Recyclable (No CFC) & 1. Vibration testing as per ISTA - 1G Non- operational with Packing	Standard Package of UPS to include the following minimum accessories	1. UPS 2. CD - Monitoring Software 3. RS232 Cable 4. Tower Stand - For use as Tower 5. Brackets for mounting in 19" IT Server / Networking Rack 6. UPS to Battery bank connecting Cable 7. User Manual	Manufacturer Certifications	QMS: As per ISO 9001: 2008 EMS: As per ISO 14001: 2004 OSHAS: As per ISO 18001: 2007	Product Safety Certifications (Mandatory)	BIS Certification IEC 62040-1:2008 ESD: IEC61000-4-2: level4 RS: IEC61000-4-3: level3 EFT: IEC61000-4-4: level4 SURGE: IEC61000-4-5: level4 CS: IEC61000-4-6: level3 IEC61000-4-8 IEC 61000-2-2 EN 62040-2:2006 EN 61000-3-2:2009 EN 61000-3-3:2013	Service Support	Three Years Warranty PAN India Service Support of OEM should be available	<p>The bidder has suggested below specifications:</p> <table border="1"> <thead> <tr> <th data-bbox="1048 256 1256 288">Item Particulars</th> <th data-bbox="1256 256 1529 288">Specifications</th> </tr> </thead> <tbody> <tr> <td data-bbox="1048 288 1256 320">Operating Humidity</td> <td data-bbox="1256 288 1529 320">20%-90% RH noncondensing</td> </tr> <tr> <td data-bbox="1048 320 1256 352">Noise Level</td> <td data-bbox="1256 320 1529 352"><50dBA</td> </tr> <tr> <td data-bbox="1048 352 1256 416">Dimension (w x d x h) in mm</td> <td data-bbox="1256 352 1529 416">D x W x H (mm): 397 x145 x220</td> </tr> <tr> <td data-bbox="1048 416 1256 448">Weight - in kg</td> <td data-bbox="1256 416 1529 448">7.4kgs</td> </tr> <tr> <td data-bbox="1048 448 1256 608">Packaging Material/ Vibration Withstand & Drop Test</td> <td data-bbox="1256 448 1529 608">Shall be as per standard design practice</td> </tr> <tr> <td data-bbox="1048 608 1256 751">Standard Package of UPS to include the following minimum accessories</td> <td data-bbox="1256 608 1529 751">Shall be as per standard design practice</td> </tr> <tr> <td data-bbox="1048 751 1256 831">Manufacturer Certifications</td> <td data-bbox="1256 751 1529 831">UPS is ISO 9001, ISO 14001, ISO 45001 certified</td> </tr> <tr> <td data-bbox="1048 831 1256 911">Product Safety Certifications (Mandatory)</td> <td data-bbox="1256 831 1529 911">As per IEC/EN 62040-1</td> </tr> <tr> <td data-bbox="1048 911 1256 1054">Service Support</td> <td data-bbox="1256 911 1529 1054">Standard 2 years warranty on UPS and battery shall be provided</td> </tr> </tbody> </table>	Item Particulars	Specifications	Operating Humidity	20%-90% RH noncondensing	Noise Level	<50dBA	Dimension (w x d x h) in mm	D x W x H (mm): 397 x145 x220	Weight - in kg	7.4kgs	Packaging Material/ Vibration Withstand & Drop Test	Shall be as per standard design practice	Standard Package of UPS to include the following minimum accessories	Shall be as per standard design practice	Manufacturer Certifications	UPS is ISO 9001, ISO 14001, ISO 45001 certified	Product Safety Certifications (Mandatory)	As per IEC/EN 62040-1	Service Support	Standard 2 years warranty on UPS and battery shall be provided	<p>No Change.</p> <p>(The bidders request is not accepted.)</p>
Item Particulars	Specifications																																											
Operating Humidity	5% ~ 95%RH (No Condensing)																																											
Noise Level	< 48 dbA at 1 meter distance																																											
Dimension (w x d x h) in mm	To be furnished by the vendor																																											
Weight - in kg	To be furnished by the vendor																																											
Packaging Material/ Vibration Withstand & Drop Test	Recyclable (No CFC) & 1. Vibration testing as per ISTA - 1G Non- operational with Packing																																											
Standard Package of UPS to include the following minimum accessories	1. UPS 2. CD - Monitoring Software 3. RS232 Cable 4. Tower Stand - For use as Tower 5. Brackets for mounting in 19" IT Server / Networking Rack 6. UPS to Battery bank connecting Cable 7. User Manual																																											
Manufacturer Certifications	QMS: As per ISO 9001: 2008 EMS: As per ISO 14001: 2004 OSHAS: As per ISO 18001: 2007																																											
Product Safety Certifications (Mandatory)	BIS Certification IEC 62040-1:2008 ESD: IEC61000-4-2: level4 RS: IEC61000-4-3: level3 EFT: IEC61000-4-4: level4 SURGE: IEC61000-4-5: level4 CS: IEC61000-4-6: level3 IEC61000-4-8 IEC 61000-2-2 EN 62040-2:2006 EN 61000-3-2:2009 EN 61000-3-3:2013																																											
Service Support	Three Years Warranty PAN India Service Support of OEM should be available																																											
Item Particulars	Specifications																																											
Operating Humidity	20%-90% RH noncondensing																																											
Noise Level	<50dBA																																											
Dimension (w x d x h) in mm	D x W x H (mm): 397 x145 x220																																											
Weight - in kg	7.4kgs																																											
Packaging Material/ Vibration Withstand & Drop Test	Shall be as per standard design practice																																											
Standard Package of UPS to include the following minimum accessories	Shall be as per standard design practice																																											
Manufacturer Certifications	UPS is ISO 9001, ISO 14001, ISO 45001 certified																																											
Product Safety Certifications (Mandatory)	As per IEC/EN 62040-1																																											
Service Support	Standard 2 years warranty on UPS and battery shall be provided																																											

Sr. No	NIT Reference	As published in NIT	Query/ Request of interested agencies	Clarifications/ Amendments Recommended by Technical Committee
3	Not Applicable	Not Applicable	Request bidders to provide tender specific authorisation certificate from OEM of major products like audio system and display.	<p><i>Since the equipment will be sourced on rental basis and their ownership will remain with agency, it shall be agency's responsibility to maintain uptime of the equipment. In addition, the equipment's to be installed must be as per the specification provided in the tender document.</i></p> <p>(The clarification as above is recommended)</p>
4	Not applicable	Not Applicable	Bidder has requested clarification if there is any Exemption for MSME in EMD payment.	<p><i>Refer clause 7.2, Section II – Instructions to Bidder which states "It may be noted that no bidder is exempted from deposit of EMD. Tenders submitted without EMD shall be summarily rejected."</i></p> <p>(The clarification as above is recommended)</p>

Shri. Sumit Biswas
Representative of SRU,
Patna, Bihar

Ms. Anuja Daniel
Principal, College of Nursing,
IGIMS, Patna

Shri Arvind Kumar
System Analyst-cum-Data officer,
State Health Society, Bihar

Dr. Y. N. Pathak
State Programme Officer (Nursing),
State Health Society, Bihar

Shri Yogendra Prasad,
Additional Director (Finance),
State Health Society, Bihar

Dr. Ravishankar Singh
Chief Medical Officer,
ROHFW (Gol), Patna

Shri. Khalid Arshad
Administrative Officer,
State Health Society, Bihar

Dr. Kaushal Kumar
Director in Chief (Nursing),
Health Services, Patna, Bihar